



**Technical features:**

- Case height 82 mm
- Zinc plated case
- Zinc plated faceplate
- Nickel-plated steel dead-bolt
- Nickel-plated, reversible latch and roller
- Drill resistant protection plate

- Nylon faceplate spacer
- Lock fixing screws
- Instruction sheet

**On request:**

- Specific striking plates


**Hand:**

0 = Non-handed

**Supplied as standard:**

- 3 keys item 1.00100.00.0 or item 1.00102.00.0
- Set of nylon key guide escutcheons item 1.06123.03.0
- Set of escutcheon fixing screws:
  - length 60 mm for the version with key item 1.00100.00.0
  - length 75 mm for the version with key item 1.00102.00.0

Type	Description	Key item	Throws	Centre Distance	Faceplate	Backset	Unit weight	Pieces	ITEM				
									Type	Dim.	Hand	Fin.	Pars. Spec.




- Dead-bolt and latch



1 00100 00 1


4 67 25 70 1,150 12 1 57312 73 0

- Dead-bolt and latch



1 00102 00 1

4 67 25 70 1,150 12 1 57312 71 0




- Dead-bolt and latch
- Pre-arranged for additional locking points
- ON REQUEST:
  - Internal ragged extended bolts item 1.06451.00.0
  - Internal straight extended bolts item 1.06451.10.0
  - External bolt connectors item 1.06452.05.0
  - Extended bolts operated by internal rods item 1.06453.05.0




1 00100 00 1

4 67 25 70 1,226 12 1 57317 73 0



1 00102 00 1

4 67 25 70 1,230 12 1 57317 71 0











- Dead-bolt and roller
- 2 to 14.5 mm. adjustable roller



1 00100 00 1

4 - 25 70 1,025 12 1 57320 73 0

Type	Description	Key item	Throws	Centre Distance	Faceplate	Backset	Unit weight Kg	Pieces	ITEM							
									Type	Dim.	Hand	Fin.	Pers.	Spec.		
	<ul style="list-style-type: none"> <li>• Dead-bolt and roller</li> <li>• 2 to 14.5 mm. adjustable roller</li> <li>• Pre-arranged for additional locking points</li> <li>• ON REQUEST:                             <ul style="list-style-type: none"> <li>- Internal ragged extended bolts item 1.06451.00.0</li> <li>- Internal straight extended bolts item 1.06451.10.0</li> <li>- External bolt connectors item 1.06452.05.0</li> <li>- Extended bolts operated by internal rods item 1.06453.05.0</li> </ul> </li> </ul>	 1 00100 00 1	4	-	25	70	1,080	12	1	57325	73	0				
		 1 00102 00 1	4	-	25	70	1,100	12	1	57325	71	0				
	<ul style="list-style-type: none"> <li>• Dead-bolt only</li> <li>• Without drill resistant plate</li> </ul>	 1 00100 00 1	4	-	25	70	1,075	12	1	57330	73	0				
		 1 00100 00 1	4	-	25	70	1,140	12	1	57335	73	0				
	<ul style="list-style-type: none"> <li>• Dead-bolt only</li> <li>• Pre-arranged for additional locking points</li> <li>• Without drill resistant plate</li> <li>• ON REQUEST:                             <ul style="list-style-type: none"> <li>- Internal ragged extended bolts item 1.06451.00.0</li> <li>- Internal straight extended bolts item 1.06451.10.0</li> <li>- External bolt connectors item 1.06452.05.0</li> <li>- Extended bolts operated by internal rods item 1.06453.05.0</li> </ul> </li> </ul>	 1 00102 00 1	4	-	25	70	1,030	12	1	57335	71	0				