A

s



AADBANED MAADBANED MAADBANED MAADBANED MAADBANED MAADBANED MAADBANED MAADBANED	CALIFIC HERE CALIFIC HERE CALIF	 Technical features: 5 pins key bitting systems Carbonitrided solid steel body, with chemical anti-corrosion nickel-plating treatment Hardened steel shackle, with chemical nickel-plating treatment The removable cylinder can be either rekeyed or replaced Carbonitrided steel plug protection plate Carbonitrided steel cylinder protection plate, with chemical nickel-plating treatment Desmopan impact resistant protection device (for the 28050 series) LIM patented key profile
Туре	Description	Key item Ke
	• Key removable in locked po	osition only 55 25,0 11,0 25,0 25,0 5 1 00401 00 1 0,565 6 1 28050 55 0 55 25,0 11,0 45,0 25,0 5 1 00401 00 1 0,601 6 1 28050 56 0 55 26,0 11,0 45,0 25,0 5 1 00401 0 1 0,601 6 1 28050 56 0 70 31,0 14,0 25,0 26,0 5 1 00401 0 1 0,880 6 1 28050 70 0 70 31,0 14,0 45,0 26,0 5 1 00401 0 1 0,927 6 1 28050 72 0
ISS	• Skin pack	55 25,0 11,0 25,0 25,0 5 1 00401 00 1 0,578 6 1 28055 55 0 55 25,0 11,0 45,0 25,0 5 1 00401 00 1 0,608 6 1 28055 56 0 55 26,0 11,0 65,0 25,0 5 1 00401 00 1 0,636 6 1 28055 57 0 70 31,0 14,0 25,0 26,0 5 1 00401 00 1 0,929 6 1 28055 70 0 70 31,0 14,0 45,0 26,0 5 1 00401 0 1 9,929 6 1 28055 71 0 70 31,0 14,0 65,0 26,0 5 1 00401 0 9,971 6 1 28055 72 0

 Key removable in locked position only 	62 2	25,0 11,0	25,0 2	5,0	5	1 00401 00 1	0,745	6	1 28350 62 0
, , ,		31,0 14,0					1,116	6	1 28350 73 0
_									

LIM STEEL PADLOCKS		An <i>(PP)</i> Ingersol Rand Company
Туре	Description	Key item ITEM A C D L S 똝 Unit weight Pieces
155	• Skin pack	62 25,0 11,0 25,0 25,0 5 1 00401 00 1 0,768 6 1 28355 62 0 73 31,0 14,0 28,0 28,0 5 1 00401 00 1 1,140 6 1 28355 73 0
)	66 20,0 10,0 11,0 25,0 5 1 00401 00 1 0,685 6 1 28550 66 0 66 18,0 14,0 17,5 28,0 5 1 00401 00 1 0,837 6 1 28550 67 0 75 27,0 12,0 13,5 28,0 5 1 00401 00 1 0,852 6 1 28550 75 0 84 36,0 12,0 17,5 28,0 5 1 00401 00 1 0,970 6 1 28550 84 0 84 36,0 14,0 17,5 28,0 5 1 00401 0 1 0,983 6 1 28550 85 0
	• Skin pack	66 20,0 10,0 11,0 25,0 5 1 00401 00 1 0,745 6 1 28555 66 0 66 18,0 14,0 17,5 28,0 5 1 00401 00 1 0,855 6 1 28555 67 0 75 27,0 12,0 13,5 28,0 5 1 00401 00 1 0,905 6 1 28555 75 0 84 36,0 12,0 17,5 28,0 5 1 00401 00 1 ,018 6 1 28555 84 0 84 36,0 14,0 17,5 28,0 5 1 00401 00 1 ,009 6 1 28555 85 0