


Technical features:

- 10 mm. thick steel front (12 mm. for the 420x550 and 490x620 versions)
- Side and upper walls in 5 mm. thick steel
- Seals are assembled using tough welds
- Nickel-plated steel dead-bolts (diameter 22 mm.)
- Special high-resistance anti-corrosion kiln painting
- Carbonitrided steel lock protection plate
- Lock and mechanisms are fixed directly onto the door of the safe.
- Opening commands do not protrude when in the rest position

Supplied as standard:


- Shelves
- Fixing grips (4 pieces)
- Instruction sheet
- Installation instructions

Type	Description	Prompt delivery	Outside dim.			Door thickness	Vertical bolts	Horizontal bolts	No. of shelves	Unit weight Kg	Pieces	ITEM			
			L	H	P							Type	Dim.	Hand	Fin.




- Key and 3-knob combinator version
- Two keys item1.00101.00.2

*	360	240	300	10	2	1	28,600	1	1	82250	34	0				
*	420	300	350	10	2	3	42,800	1	1	82250	43	0				
*	490	360	350	10	2	3	55,000	1	1	82250	53	0				
	360	490	400	10	2	3	59,000	1	1	82250	74	0				
	420	550	450	12	2	3	75,750	1	1	82250	85	0				
	490	620	450	12	2	3	93,080	1	1	82250	95	0				




- Key and single-operation combinator version
- Two keys item1.00101.00.2

*	360	240	300	10	2	1	29,000	1	1	82350	34	0				
	420	300	350	10	2	3	41,500	1	1	82350	43	0				
	490	360	350	10	2	3	55,200	1	1	82350	53	0				
	360	490	400	10	2	3	59,850	1	1	82350	74	0				
	420	550	450	12	2	3	76,750	1	1	82350	85	0				
	490	620	450	12	2	3	92,000	1	1	82350	95	0				



- 3-knob combinator only version

	360	240	300	10	2	1	28,600	1	1	82450	34	0				
	420	300	350	10	2	3	42,200	1	1	82450	43	0				
	490	360	350	10	2	3	53,800	1	1	82450	53	0				
	360	490	400	10	2	3	58,700	1	1	82450	74	0				
	420	550	450	12	2	3	75,600	1	1	82450	85	0				
	490	620	450	12	2	3	92,500	1	1	82450	95	0				



- Single operation combinator only version

	360	240	300	10	2	1	28,800	1	1	82550	34	0				
	420	300	350	10	2	3	42,900	1	1	82550	43	0				
	490	360	350	10	2	3	54,800	1	1	82550	53	0				
*	360	490	400	10	2	3	59,450	1	1	82550	74	0				
	420	550	450	12	2	3	76,250	1	1	82550	85	0				
	490	620	450	12	2	3	92,050	1	1	82550	95	0				