

Technical features:

- Zinc-plated steel case and striker
- Brass latch and dead-bolt
- Brass draw-back pull and knob

Supplied as standard:

- Striker
- Fixing screws
- 3 keys item 1.01310.00.1













On request:











- Protective back plate and striker spacer item 1.07061.10.0

Hand:

1 = R.H. inwards

2 = L.H. inwards

Type	Description	Cylinder	Throws	Backset	Unit weight 	Pieces 	ITEM				
							Type	Dim.	Hand	Fin. Pers. Spec.	
 <ul style="list-style-type: none"> • With fixing tongue • Inside knob and draw-back pull 		 1 02552 50 0	2	60	1,050	1	1	50411	60	1	
			2	60	1,050	1	1	50411	60	2	
			2	70	1,120	1	1	50411	70	1	
			2	70	1,120	1	1	50411	70	2	
 <ul style="list-style-type: none"> • With fixing tongue • Inside draw-back pull 		 1 02106 00 0	2	60	1,050	1	1	50421	60	1	
			2	60	1,050	1	1	50421	60	2	
			2	70	1,120	1	1	50421	70	1	
			2	70	1,120	1	1	50421	70	2	
 <ul style="list-style-type: none"> • With fixing tongue • Inside draw-back pull 		 1 02106 00 0	2	50	0,965	1	1	50461	50	1	
			2	50	0,975	1	1	50461	50	2	
 <ul style="list-style-type: none"> • With fixing tongue • Through spindle 		 1 02106 00 0	2	60	1,150	1	1	50471	60	1	
			2	60	1,170	1	1	50471	60	2	
 <ul style="list-style-type: none"> • With fixing tongue • Inside knob • Through spindle 		 1 02552 50 0	2	60	1,150	1	1	50481	60	1	
			2	60	1,160	1	1	50481	60	2	

Type	Description	Cylinder	Throws	Backset	Unit weight Kg	Pieces	ITEM				
							Type	Dim. Hand	Fin.	Pers.	Spec.
 <ul style="list-style-type: none"> • Without fixing tongue • Inside knob and draw-back pull 		 1 02552 50 0	2	60	1,020	1	1 50511	60	1		
			2	60	1,020	1	1 50511	60	2		
			2	70	1,090	1	1 50511	70	1		
			2	70	1,090	1	1 50511	70	2		
 <ul style="list-style-type: none"> • Without fixing tongue • Inside draw-back pull 		 1 02106 00 0	2	60	1,010	1	1 50521	60	1		
			2	60	1,040	1	1 50521	60	2		
			2	70	1,080	1	1 50521	70	1		
			2	70	1,080	1	1 50521	70	2		
 <ul style="list-style-type: none"> • Without fixing tongue • Inside draw-back pull 		 1 02106 00 0	2	50	0,950	1	1 50561	50	1		
			2	50	0,955	1	1 50561	50	2		
 <ul style="list-style-type: none"> • Without fixing tongue • Through spindle 		 1 02106 00 0	2	60	1,110	1	1 50571	60	1		
			2	60	1,120	1	1 50571	60	2		
 <ul style="list-style-type: none"> • Without fixing tongue • Inside knob • Through spindle 		 1 02552 50 0	2	60	1,130	1	1 50581	60	1		
			2	60	1,120	1	1 50581	60	2		