



Technical features:

- Zinc-plated case
- Zinc-plated faceplate
- Nickel-plated steel dead-bolt

Supplied as standard:

- Inside steel escutcheon item 1.06124.02.0
- Instruction sheet


On request:

- Zinc-plated steel striking plate item 1.06232.00.0

Hand:

0 = Non-handed

Type	Description	Key item	Throws	Centre Distance	Faceplate Backset	Unit weight Kg	Pieces	ITEM				
								Type	Dim.	Hand	Fin.	Pers. Spec.



- Case height 82 mm.
- 2 keys



1 00100 00 1


4	-	25	52	0,788	12	1	57013	50	0	00	30
4	-	25	60	0,833	12	1	57013	60	0	00	30
4	-	25	70	0,868	12	1	57013	70	0	00	30

- As above, keyed alike (KA)
- 1 key



1 00100 00 1

4	-	25	52	0,760	12	1	57013	52	0	00	30
4	-	25	60	0,812	12	1	57013	62	0	00	30
4	-	25	70	0,833	12	1	57013	72	0	00	30



- Case height 82 mm.
- 2 keys
- Pre-arranged for additional locking points
- Pair of threaded bushings (M8) item 1.06290.10.0
- ON REQUEST:
 - Extended bolts item 1.06415.00.0
 - Extended bolts item 1.07088.03.0
 - Floor striker item 1.06086.00.0
 - Floor striker with dust cover item 1.06086.02.0



1 00100 00 1


4	-	25	60	0,940	12	1	57016	60	0		
4	-	25	70	0,982	12	1	57016	70	0		

- As above, keyed alike (KA)
- 1 key



1 00100 00 1

4	-	25	60	0,925	12	1	57016	62	0		
4	-	25	70	0,963	12	1	57016	72	0		



- Case height 82 mm.
- 2 keys Dead-bolt with 3 locking points



1 00100 00 1










4	-	25	60	0,754	12	1	57030	60	0		
4	-	25	70	0,780	12	1	57030	70	0		

- As above, keyed alike (KA)
- 1 key



1 00100 00 1

4	-	25	60	0,735	12	1	57030	62	0		
4	-	25	70	0,773	12	1	57030	72	0		

Type	Description	Key item	Throws	Centre Distance	Faceplate	Backset	Unit weight Kg	Pieces	ITEM							
									Type	Dim.	Hand	Fin.	Pers. Spec.			
	<ul style="list-style-type: none"> • Case height 82 mm. • 2 keys • Dead-bolt with 3 locking points • Pre-arranged for additional locking points • Pair of threaded bushings (M8) item 1.06290.10.0 • ON REQUEST: <ul style="list-style-type: none"> - Extended bolts item 1.06415.00.0 - Extended bolts item 1.07088.03.0 - Floor striker item 1.06086.00.0 - Floor striker with dust cover item 1.06086.02.0 	 1 00100 00 1	4	-	25	60	0,848	12	1	57035	60	0				
			4	-	25	70	0,919	12	1	57035	70	0				
		 1 00100 00 1	<ul style="list-style-type: none"> • As above, keyed alike (KA) • 1 key 	4	-	25	60	0,838	12	1	57035	62	0			
				4	-	25	70	0,870	12	1	57035	72	0			
					<ul style="list-style-type: none"> • Case height 93 mm. • 2 keys 	 1 00100 00 1	2	-	22	40	0,520	12	1	57223	40	0
							2	-	22	45	0,540	12	1	57223	45	0
2	-	22	50				0,560	12	1	57223	50	0				
2	-	22	60				0,592	12	1	57223	60	0				
 1 00100 00 1	<ul style="list-style-type: none"> • As above, keyed alike (KA) • 1 key 	2	-			22	40	0,506	12	1	57223	42	0			
		2	-			22	45	0,524	12	1	57223	47	0			
		2	-			22	50	0,545	12	1	57223	52	0			
		2	-			22	60	0,578	12	1	57223	62	0			
	<ul style="list-style-type: none"> • Case height 93 mm. • 2 keys • Pre-arranged for additional locking points • Pair of threaded bushings (M8) item 1.06290.10.0 • ON REQUEST: <ul style="list-style-type: none"> - Extended bolts item 1.06415.00.0 - Extended bolts item 1.07088.03.0 - Floor striker item 1.06086.00.0 - Floor striker with dust cover item 1.06086.02.0 	 1 00100 00 1	2	-	25	45	0,670	12	1	57226	45	0				
			2	-	25	50	0,687	12	1	57226	50	0				
			2	-	25	60	0,730	12	1	57226	60	0				
		 1 00100 00 1	<ul style="list-style-type: none"> • As above, keyed alike (KA) • 1 key 	2	-	25	45	0,657	12	1	57226	47	0			
				2	-	25	50	0,664	12	1	57226	52	0			
				2	-	25	60	0,708	12	1	57226	62	0			