

**Technical features:**

- Stainless steel case
- Special stainless zinc alloy body
- Transversally adjustable striker, by 2 mm
- Hold-open device
- Hold-open catch mechanism
- 12 V ac CE

**Supplied as standard:**

- No. 2 nylon, 3 mm faceplate spacers
- Instruction sheet


1 = R.H. inwards


L.H. outwards


2 = L.H. inwards

R.H. outwards

Type	Description	Faceplate	Unit weight	Pieces	ITEM				
					Type	Dim.	Hand	Fin.	Pers.

	<ul style="list-style-type: none"> <li>• Flat faceplate 25 x 3 mm.</li> <li>• External non-repeating device with spring-operated rod</li> <li>• For locks with latch:                             <ul style="list-style-type: none"> <li>- series 44600, 46000, 48000, 57300</li> </ul> </li> <li>• ON REQUEST:                             <ul style="list-style-type: none"> <li>- faceplate spacer from 3 mm. item 1.06141.84.0</li> </ul> </li> </ul>	25	0,338	1	1	15020	00	1		
		25	0,320	1	1	15020	00	2		

	<ul style="list-style-type: none"> <li>• Flat faceplate 34 x 2 mm.</li> <li>• External non-repeating device with spring-operated rod</li> <li>• For locks with latch:                             <ul style="list-style-type: none"> <li>- series 44600, 46000, 48000, 57300</li> </ul> </li> <li>• ON REQUEST:                             <ul style="list-style-type: none"> <li>- faceplate spacer from 3 mm. item 1.06141.85.0</li> </ul> </li> </ul>	34	0,350	1	1	15021	00	1		
		34	0,350	1	1	15021	00	2		

	<ul style="list-style-type: none"> <li>• Flat faceplate 25 x 3 mm.</li> <li>• Built-in non-repeating device</li> <li>• For locks with latch:                             <ul style="list-style-type: none"> <li>- series 44600, 46000, 48000, 57300</li> </ul> </li> <li>• ON REQUEST:                             <ul style="list-style-type: none"> <li>- faceplate spacer from 3 mm. item 1.06141.84.0</li> </ul> </li> </ul>	25	0,338	1	1	15030	00	1		
		25	0,338	1	1	15030	00	2		