


**Technical features:**

- 10 mm. thick steel front (12 mm. for the 420x550 and 490x620 versions)
- Side and upper walls in 5 mm. thick steel
- Seals are assembled using tough welds
- Nickel-plated steel dead-bolts (diameter 22 mm.)
- Special high-resistance anti-corrosion kiln painting
- Carbonitrided steel lock protection plate
- Lock and mechanisms are fixed directly onto the door of the safe

**Supplied as standard:**

- Shelves
- Fixing grips (4 pieces)
- Instruction sheet
- Installation instructions

Type	Description	Prompt delivery	Outside dim.			Door thickness	Vertical bolts	Horizontal bolts	No. of shelves	Unit weight 	Pieces 	ITEM			
			L	H	P							Type	Dim.	Hand	Fin.



- Key only version
- Two keys item 1.00101.00.2

	360	240	300	10	2	1	28,300	1	<b>1 82050 34 0</b>
	420	300	350	10	2	3	40,650	1	<b>1 82050 43 0</b>
	490	360	350	10	2	3	54,000	1	<b>1 82050 53 0</b>
*	360	490	400	10	2	3	57,000	1	<b>1 82050 74 0</b>
	420	550	450	12	2	3	75,700	1	<b>1 82050 85 0</b>
	490	620	450	12	2	3	92,000	1	<b>1 82050 95 0</b>